



BLT250/300


BATTERY DISCHARGER

PBM Group

- ▶ battery chargers
- ▶ dischargers
- ▶ managing systems
- ▶ monitoring
- ▶ accessories

pbmbatterychargers.com

P.B.M. Srl
Via Barella Z.I.
41058 Vignola (Modena) ITALY

 +39 059 7705311

 info@gruppopbm.it



- ▶ Automatic Charging and Discharging Cycles Management
- ▶ Battery and Charger Double Connection
- ▶ BLT300 Battery voltage range 2V to 96V max 300A
- ▶ BLT250 Battery voltage range 2V to 120V max 250A
- ▶ Battery voltage and discharge current are easily programmable through switch
- ▶ All functions can be programmed in local mode by keyboard and multifunctions display
- ▶ PC can be connected to store data concerning charge and discharge cycles
- ▶ Suitable for Battery Efficiency test , Battery Regeneration, Desulphation process

BATTERY DISCHARGER

MODEL

BLT250/300

<i>Model</i>	<i>Battery (V)</i>	<i>Main (A)</i>
<i>BLT3K</i>	<i>4 ÷ 120</i>	<i>2 ÷ 160</i>
<i>BLT160</i>	<i>4 ÷ 96</i>	<i>2 ÷ 160</i>
<i>BLT125</i>	<i>4 ÷ 120</i>	<i>2 ÷ 125</i>
<i>BLT250</i>	<i>4 ÷ 120</i>	<i>2 ÷ 250</i>
<i>BLT300</i>	<i>4 ÷ 96</i>	<i>2 ÷ 300</i>