



HF9 MULTITENSION

BATTERY CHARGER

PBM Group

- ▶ battery chargers
- ▶ dischargers
- ▶ managing systems
- ▶ monitoring
- ▶ accessories

pbmbatterychargers.com

P.B.M. Srl
Via Barella Z.I.
41058 Vignola (Modena) ITALY

 +39 059 7705311

 info@gruppopbm.it



- ▶ Three Phase 400VAC +/-10% 9KW power
- ▶ Available on request 230/440/480VAC 3phase
- ▶ Suitable for battery from 2-96V max 80A
- ▶ Available on 12Kw and 16KW power.
- ▶ Microprocessor-controlled Charging process
- ▶ Different types of curves:
CYCLIC P, CYCLIC Pb GEL, CYCLIC NiCd
CYCLIC LiPO, CYCLIC AGM, DESULPHATION
- ▶ Multifunctional LCD Display
- ▶ Failure diagnostic by means of LED's and LCD
- ▶ Protection against battery polarity inversion
- ▶ Stored charges

BATTERY CHARGER

MODEL

HF9 MULTITENSION

<i>Model</i>			
<i>9KW</i>	<i>2-48V max 150A</i>	<i>2-80V max 90A</i>	<i>2-120V max 60A</i>
<i>16KW</i>	<i>2-48V max 250A</i>	<i>2-80V max 160A</i>	<i>2-120V max 100A</i>

Other specials models availables on request